

# E3/L3



## OMNI GRIP+

Standard E3/L3 rock lug pattern combines excellent traction and high resistance to wear and cutting. Excellent traction in all off-road conditions. Thick undertread for improved puncture resistance. High quality carcass allows for excellent retreadability. Wear and cut resistant tread compound.

Engineered for:  
Loaders \ Dump Trucks \ Graders



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 mph	
17.5R25	**	TL	14.00/1.5	53.1	17.5	32	94	18700	76	12000	182A2/167B
				1349	444	25	650	8500	525	5450	
20.5R25	**	TL	17.00/2.0	58.8	20.5	35	94	25400	76	16100	193A2/177B
				1493	521	28	650	11500	525	7300	
23.5R25	**	TL	19.50/2.5	63.3	23.5	39	94	32000	76	20400	201A2/185B
				1608	597	31	650	14500	525	9250	
26.5R25	**	TL	22.00/3.0	68.9	26.5	43	94	40800	76	25400	209A2/193B
				1750	673	34	650	18500	525	11500	
29.5R25	**	TL	25.00/3.5	73.8	29.5	47	94	49400	76	30900	216A2/200B
				1874	749	37	650	22400	525	14000	