



# R4

# SUPER SKID

The Super Skid is the standard bearer of the DYNAMAMAXX family of skid steer tires with the versatile R4 bias ply. Proven to be one of the lowest cost-per-hour R4 tire, the Super Skid is built with a wear resistant compound, superior tread design, super sidewall and rim shield protector.

Engineered for:

Skid Steer \ Aerial Boom Lift \ Scissor Lifts \ Compact Tractors \ Mining \ Front Backhoe \ 3-Wheel Forklifts



| Size       | PR | Type | Rim   | O.D. | S.W  | T.D.  | Infl. P. | L.C.C. (lbs/kg) |        |
|------------|----|------|-------|------|------|-------|----------|-----------------|--------|
|            |    |      |       | in   | in   | 32nds | psi      | 5 mph           | 30 mph |
|            |    |      |       | mm   | mm   | mm    | KPa      | 10 kph          | 50 kph |
| 27x8.50-15 | 8  | TL   | 7.00  | 26.7 | 8.7  | 18    | 60       | 2875            | 1820   |
|            |    |      |       | 678  | 221  | 14    | 415      | 1305            | 825    |
| 10-16.5    | 10 | TL   | 8.25  | 30.2 | 10.6 | 21    | 75       | 4710            | 3200   |
|            |    |      |       | 767  | 269  | 17    | 515      | 2135            | 1450   |
| 12-16.5    | 12 | TL   | 9.75  | 32.7 | 13   | 26    | 80       | 6320            | 3980   |
|            |    |      |       | 830  | 330  | 21    | 550      | 2865            | 1800   |
| 14-17.5    | 14 | TL   | 10.50 | 36.2 | 14.1 | 33    | 80       | 8540            | 5380   |
|            |    |      |       | 919  | 358  | 26    | 550      | 3875            | 2440   |
| 15-19.5    | 14 | TL   | 12.25 | 40.1 | 15.5 | 33    | 70       | 10060           | 6340   |
|            |    |      |       | 1018 | 394  | 26    | 480      | 4565            | 2875   |

